

# ScorVac 10L

## VACUUM FEATURES

- Vacuum system designed for a variety of operations
- Recovers a wide range of viscous materials
- Robust build, light-weight and easy assembly
- Multiple nozzles options
- 60 m<sup>3</sup>/h capacity



The ScorVac 10L Portable Vacuum System is a powerful suction tool that recovers viscous liquids including hydrocarbons, oil emulsions, oiled mud and contaminated soil/sand with an oil recovery rate of over 60 m<sup>3</sup>/h. The vacuum is ideal for on-land operations including beach cleaning, pipeline spills and other operations where oil must be removed from a surface, especially in locations where access is limited for heavy machinery and equipment. A variety of nozzles allow the operator to select the right suction inlet for the operation at hand. The system employs a robust build intended for long-term use in demanding operations.

- Generates up to 90% vacuum
- The vacuum has a hydraulic, electric or diesel-driven vacuum pump
- The complete vacuum system consists of a Hot-Dip Galvanized (HDG) hopper tank, an aluminum vacuum dome head, hoses, aluminum suction lance and a multiple nozzle set
- The nozzle set includes a fan nozzle and a straight nozzle; weir head optional addition
- Requires minimal assembly/disassembly allowing easy maintenance
- Quick couplings allow for rapid assembly

## TECHNICAL SPECIFICATIONS

Oil Recovery Rate	60 m <sup>3</sup> /h
Vacuum Pump Capacity	318 m <sup>3</sup> /h
Suction Height	8 m
Hopper Volume	2 - 5 m <sup>3</sup>
Operating Pressure (max.)	0.5 bar
Vacuum (max.)	90%
Weight (diesel/hydraulic)	170.8/130 kg
Length (diesel/hydraulic)	1.01/0.98 m
Width (diesel/hydraulic)	0.68/0.53 m
Height (diesel/hydraulic)	0.78/0.53 m

\*Volume dependent on customer selection

## SYSTEM APPLICATIONS

- Shoreline
- Inland waters
- Ports & Harbors
- Tight Spaces
- Tank Cleaning
- Pipeline

## SYSTEM COMPONENTS

- Hopper Tank
- Dome Head
- Suction Lance
- Nozzle(s)
- Transfer Pump
- Transfer Hoses