



The ScorTank Framed (4, 8, 10) is a rectangular, open top temporary tank supported by an aluminium frame designed to store hydrocarbons and other liquids. It is quickly assembled and is designed for multiple applications including on-board vessels, beaches, jetties and most other work platforms. The design evenly distributes the weight of stored liquids. The storage tank is portable with no tools required for assembly. It is maintenance free other than cleaning after use. It is equipped with a 1 ½" Plastic Decanting Valve for easy drainage and to simplify operations.



TECHNICAL SPECIFICATIONS			
Model	4	8	10
Capacity	4 m ³	8 m ³	10 m ³
Frame	Tubular, Marine-Grade Aluminium or Neoprene/Rubber		
Dimensions Deployed (LxWxH)	2.6 x 2 x 0.9 m	4.9 x 2.1 x 0.9 m	4.4 x 2.6 x 2.8 m
Dimensions Stored (LxWxH)	2.5 x 1 x 0.3 m	2.6 x 1 x 0.3m	2.8 x 1 x 0.3 m
Weight	50.8 kg	54.7 kg	76.8 kg
Base Fabric	Polymer Coated Polyester Fabric or Neoprene/Rubber		
Fabric Weight	1000 gr/m ²		
Drainage	Plastic Decanting Valve		

APPLICATION OPTIONS:

Decontamination

- Hydrocarbon Storage
- Recovered Liquid Storage
- Water Storage
- · Decanting Water from Oil

EQUIPMENT OPTIONS:

- Beaches
- Nearshore
- Ports & Harbours
- Off-shore
- Vessels

TECHNICAL DATA

The tank is manufactured from Polymer Alloy Coated Polyester fabric. The tubular space frame is manufactured with marine-grade aluminium. It is fitted with a decanting valve for easy drainage. A tarpaulin ground mat provides protection from spills during transfer operations. It comes in a heavy-duty, PVC Bag for storage and transportation. It is easily cleaned and is resistant to sea-water, UV radiation, chemical dispersant and hydrocarbons.

KEY FEATURES:

- Quick set-up
- Compact storage
- Light-weight, portable and easily transported
- Resistant to wear, tear and hydrocarbon damage
- Decanting valve



